

For - BEVERAGE & FOOD / COSMETIC / PHARMACEUTICALS / CHEMISTRY / METROLOGY

GBBT-1 Glass Bottle Burst Tester

(Explosion tester for glass bottles)





Testing interface

CYCLE4						
A = pressure level 1:	5.0	bar / Step 1:	10	sec / Rate 1:	6.0	bar/sec
pressure level 2 :	10.0	bar / Step 2:	10	sec / Rate 2:	6.0	bar/sec
pressure level 3:	15.0	bar / Step 3:	10	sec / Rate 3:	6.0	bar/sec
pressure level 4:	20.0	bar / Step 4:	10	sec / Rate 4:	6.0	bar/sec
B = pressure level 1:	20.0	bar / Step 1:	5	sec / Rate 1:	5.0	bar/sec
pressure level 2 :	30.0	bar / Step 2:	5	sec / Rate 2:	5.0	bar/sec
pressure level 3 :	40.0	bar / Step 3:	5	sec / Rate 3:	5.0	bar/sec
pressure level 4 :	50.0	bar / Step 4:	5	sec / Rate 4:	5.0	bar/sec
C = pressure level 1:	20.0	bar / Step 1:	5	sec / Rate 1:	5.0	bar/sec
pressure level 2 :	30.0	bar / Step 2:	5	sec / Rate 2:	5.0	bar/sec
pressure level 3 :	40.0	bar / Step 3:	5	sec / Rate 3:	5.0	bar/sec
pressure level 4 :	50.0	bar / Step 4:	5	sec / Rate 4:	5.0	bar/sec
D = pressure level 1:	10.0	bar / Step 1:	10	sec / Rate 1:	5.0	bar/sec
pressure level 2 :	20.0	bar / Step 2:	10	sec / Rate 2:	5.0	bar/sec
pressure level 3:	30.0	bar / Step 3:	10	sec / Rate 3:	5.0	bar/sec
pressure level 4:	40.0	bar / Step 4:	10	sec / Rate 4:	5.0	bar / sec
PREVIOUS				MENU		

Cycle setting interface

The GBBT-1 is an instrument for testing the internal pressure resistance of glass containers. It has been widely used by the glass container manufacturers and users. As a standard testing instrument for the glass container industry, it offers an important technical reference to the manufacturers for maintaining or improving the product quality and performance.

Designed for easy operation and maintenance, comply with the testing standard of ISO 7458:2004.

The pressure test of containers is made up to a predefined pressure point (trial test) or until destruction.

Characteristics:

- PLC integrated & Touch screen control
- User defined test cycle (up to 4 steps of pressure and holding time) satisfies different test request
- Automatic clamping and filling system
- · Easy operation
- · Easy sample installing, with auto clamping and water filling system
- Linear pressurization
- · Can store 10 operators and 30 products
- User defines the product lot number and sequence number
- Review the real-time testing curve
- Stainless steel design ensures the durability of tester
- Advanced safe door design ensures the safety of operator during a test.
- Special trash bin design makes the glass trash collection easily.
- RS232 output
- Can be connected to either printer or software

CE

For - BEVERAGE & FOOD / COSMETIC / PHARMACEUTICALS / CHEMISTRY / METROLOGY





Multi-Testing Cycles

Testing Chamber



Auto filling & clamping system

Trash bin design with silencing sifter

Technical specifications:

Measuring range: 0-57 bar (each station)

Resolution: 0.1 bar

Sample range: by order

Power: 115 V / 230 V, 50-60Hz

Dimension: 620 (L) × 570 (W) × 820 (H) mm

Net weight: 70 kg


Optional parts:

Compatible clamping system

Professional Software for GBBT-1



Compatible clamping system (Optional)



Professional Software for GBBT-1 (Optional)